



INLINE SERIES - 3000 HEATED 600mm SQUARE IN COUNTER

MODELS

- IN-3H06-SQ-FF-IC | 3000 Series heated 600m square, with fixed front glass, in counter
- IN-3H06-SQ-SD-IC | 3000 Series heated 600mm square, with sliding glass doors, in counter

OPTIONS [F=Factory Fitted]

- LED lighting to shelves (F)

ACCESSORIES [A=Accessory]

- Small goods tray (A)
- Toughened glass shelves (A)
- Angled base shelf (A)
- Thermal divider panels (A)
- Chicken trays (A)
- Rear decks (A)
- Stainless steel flat trays (A)
- Pie chutes and dividers (A)

OVERVIEW

Created as a medium duty solution for café, kiosk and c-store, **Inline 3000 Series** cabinets provide a plug and go solution. A range of installation options is available to make it easy to integrate the display cabinets in your retail space: in counter, on counter, or freestanding. This Cabinet Series is tested to 60 door openings an hour while still maintaining core product temperatures for food safety. Developed using FPG's world class design expertise to extend shelf life and help you sell more. Optimised for energy efficiency and to deliver the lowest total cost of ownership over the life of the cabinet. A proven performer.

FEATURES

- High energy efficiency - 0.6 kWh per hour average
- Cabinet maximum temperature range +30°C - +90°C
- Recommended core product temperature > +65°C
- Sliding doors (staff side) and fixed front or sliding doors options (customer side)
- Two adjustable shelves and base for product display
- 25,000 hour LED lighting to cabinet top and optional shelf lighting available
- Low wattage high density elements for even temperature distribution
- Unique shelf mounted ticket strip front and rear
- Fully double glazed for energy efficiency
- Also available as a on counter model or a freestanding model with a chassis



SHOWING : 3000 SERIES HEATED 600mm SQUARE, WITH FIXED FRONT, IN COUNTER

| | | | | |
|------------------|-------------------------------|---------------|-----------------------|-------------|
| IN-3H06-SQ-FF-IC | ENVIRONMENTAL TEST CONDITIONS | 22°C / 65% RH | MAX TEMPERATURE RANGE | +30°C-+90°C |
| IN-3H06-SQ-SD-IC | | | | |

FPG heated food display cabinets are designed to meet and exceed:
 · International safety standards for electrical heated appliances: IEC 60335-1, IEC 60335-2-49, IEC 60335-2-50, and the equivalent country-specific standards including AS/NZS and BS EN.
 · International standards for electromagnetic compatibility/emissions: CISPR 14-1, and the equivalent county-specific standards including AS/NZS CISPR and BS EN 55014-1.
 · Essential safety requirements: AS/NZS 3820 and AS/NZS 4417.
 Please contact FPG to discuss your requirements for meeting country-specific standards.



FPGWORLD.COM



INLINE SERIES - 3000 HEATED 600mm SQUARE IN COUNTER

SPECIFICATIONS

Heated Data

| | ENVIRONMENTAL TEST CONDITIONS | RECOMMENDED CORE PRODUCT TEMP | MAX TEMP RANGE | HEATING |
|------------------|-------------------------------|-------------------------------|----------------|----------------------------------|
| IN-3H06-SQ-FF-IC | 22°C / 65% RH | > +65°C | +30°C - +90°C | High density low wattage element |
| IN-3H06-SQ-SD-IC | 22°C / 65% RH | > +65°C | +30°C - +90°C | High density low wattage element |

Electrical Data

| | VOLTAGE | PHASE | CURRENT | kWh per hour [average] | MAINS CONNECTION | MAINS CONNECTION PLUG | IP RATING | LED LIGHTING |
|------------------|-----------|--------|---------|------------------------|----------------------|-----------------------|-----------|---------------|
| IN-3H06-SQ-FF-IC | 220-240 V | Single | 3.7 A | 0.6 kWh per hour | 3 metre 3 core cable | 10 amp, 3 pin plug | IP 20 | 25,000 hr LED |
| IN-3H06-SQ-SD-IC | 220-240 V | Single | 3.7 A | 0.6 kWh per hour | 3 metre 3 core cable | 10 amp, 3 pin plug | IP 20 | 25,000 hr LED |

Display

| | DISPLAY AREA | NO. OF SHELVES | ACCESS - FRONT | ACCESS - REAR | CONSTRUCTION |
|------------------|--------------------|----------------|----------------|---------------|---------------------|
| IN-3H06-SQ-FF-IC | 0.56m ² | 2 + Base | Fixed front | Sliding doors | 304 Stainless Steel |
| IN-3H06-SQ-SD-IC | 0.56m ² | 2 + Base | Sliding doors | Sliding doors | 304 Stainless Steel |

Dimensions [Uncrated and Crated]

| | H x W x D mm [Uncrated] | MASS [Uncrated] | H x W x D mm [Crated] | MASS [Crated] | CUBIC VOLUME [Crated] |
|------------------|-------------------------|-----------------|-----------------------|---------------|-----------------------|
| IN-3H06-SQ-FF-IC | 774 x 600 x 662 | 72 kg | 934 x 674 x 736 | 105 kg | 0.46m ³ |
| IN-3H06-SQ-SD-IC | 774 x 600 x 662 | 72 kg | 934 x 674 x 736 | 105 kg | 0.46m ³ |

Installation note:

Model cutout dimensions:

- IN-3H06-SQ-FF-IC and IN-3H06-SQ-SD-IC models require 578 x 650mm benchtop cutout (see product manual for installation guide)

In line with policy to continually develop and improve its products, Future Products Group reserves the right to change specifications and design without notice.

For more information and technical data, including installation documents, please refer to the website - www.fpgworld.com

