



FPGWORLD.COM

visair

SLIMLINE 900 OPEN FRONT REFRIGERATED: R449A

RANGE	VISAIR SLIMLINE
TEMPERATURE	REFRIGERATED
MODEL	IN-VSL09-A001
No. OF LEVELS	4 SHELVES + BASE
FRONT	OPEN FRONT
INSTALLATION	FREESTANDING/ROLLERS
REFRIGERATION	INTEGRAL, R449A
HEIGHT	2074mm
WIDTH	890mm
DEPTH	561mm

CORE PRODUCT TEMPERATURE	+2°C - +4°C
ENVIRONMENTAL TEST CONDITIONS	CLIMATE CLASS 3 25°C / 60% RH
CABINET CLASSIFICATION	3M1

ENERGY EFFICIENCY	
NZ & AU (R449A)	
For Star Rating, please visit reg.energyrating.gov.au/comparator	

FEATURES

- High energy efficiency: 1.11 kWh per hour (average)**
- Maintains an average of +2°C - +4°C core product temperature at Climate Class 3 25°C/60%RH**
- Robust open front display, powdercoated satin black with a combination of brushed and polished stainless steel for the interior
- Ultra slim footprint at 561mm depth;
 - ideal for maximising product facings with reduced stock holdings in space-constrained environments

Open Front Refrigerated Display

- Five full-width display levels: four shelves and base are full cabinet width to support maximum display capacity
- 50,000 hour powerful LED top and side lighting at 2480 lumens per metre focuses buyer attention on displayed products
- Ticket strip to shelves and base: 30mm

Operational Excellence

- Constructed from stainless and mild steel for maximum energy efficiency, climate control and durability
- Cabinet features an 'air curtain' to retain cold air within cabinet
- Configured with a pre-filter - with regular cleaning by operations staff the life of the cabinet can be extended
- Auto Condensate Removal (ACR)
- Fitted with unidirectional rollers and adjustable stabilisers



Showing : Visair Slimline refrigerated 900mm freestanding open front with four shelves and base

OPTIONS & ACCESSORIES

Contact a [FPG Sales Representative](#) for our full range, including:

- Remote refrigeration with TX, EPR or Solenoid valves for connection. Further refrigerants supported
- Add additional shelf
- Shelf: Colour and woodprint options available
- Custom colour
- Branded decals
- Night curtain
- Buffer rail
- Custom joinery solution



Please contact FPG to discuss your requirements for meeting country-specific standards.

FPGWORLD.COM



FPGWORLD.COM

visair

SLIMLINE 900 OPEN FRONT REFRIGERATED: R449A

REFRIGERATION DATA

MODEL	CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	REFRIGERATION	REFRIGERANT	REFRIGERANT CHARGE	CONDENSATE REMOVAL
IN-VSL09-AXXX	+2°C - +4°C	Climate Class 3 - 25°C / 60% RH	Integral	R449A	See serial label	ACR

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24H (kWh)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG†	HOURS	LUMENS	COLOUR
IN-VSL09-AXXX	220-240 V	Single	8.5 A	26.69	111	IP X0	3 metre 3 core cable	10 amp 3 pin plug	50,000	2480 per metre	Natural

†Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	(Ø) 66mm CAN CAPACITY	(Ø) 60mm BOTTLE CAPACITY	CHASSIS CONSTRUCTION
IN-VSL09-A001	1.23 m ²	4 Shelves + Base	Open front	N/A	240	325	Stainless 304 and mild steel


DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-VSL09-AXXX	2074 x 890 x 561	295 kg


Crated weights and dimensions vary. Please contact us for information on your shipment.

Installation note: Designed to be installed as a stand alone unit.


UNOBSTRUCTED AIRFLOW MUST BE MAINTAINED TO ENSURE UNIT PERFORMANCE AND TO MAINTAIN WARRANTY. CABINET MUST BE BOLTED TO THE FLOOR FOR SECURE INSTALLATION. PLEASE REFER TO MANUAL FOR FULL INSTALLATION INSTRUCTIONS.




PLAN





PLAN VIEW - AIRFLOW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at sales@fpgworld.com or visit www.fpgworld.com for full contact details for your region.



Worldwide contact details: