

visair

UPRIGHT 700 OPEN FRONT

REFRIGERATED: R290

RANGE	VISAIR UPRIGHT	
TEMPERATURE	REFRIGERATED	
MODEL	IN-VA07-BXXX	
FRONT	OPEN FRONT	
INSTALLATION	FREESTANDING/ROLLERS	
REFRIGERATION	INTEGRAL, R290	
HEIGHT	1431mm	
WIDTH	706mm	
DEPTH	816mm	

CORE PRODUCT TEMPERATURE	+2°C - +4°C
ENVIRONMENTAL TEST CONDITIONS	CLIMATE CLASS 3 25°C / 60% RH
CABINET CLASSIFICATION	ЗМО

ENERGY EFFICIENCY						
NZ & AU	EU					
For Star Rating, please visit:	For EPREL Rating, please visit:					
reg.energyrating.gov.au/ comparator						

FEATURES

- High energy efficiency: 0.65 kWh per hour (average)
- Maintains an average of +2°C +4°C core product temperature at Climate Class 3: 25°C/60%RH
- Robust open front display, powdercoated satin black for a sleek finish

Open Front Refrigerated Display

- Four full-width display levels: three shelves and base are powdercoated black with textured stipple finish and full cabinet width to support maximum display capacity
- 🔽 Pluggable 50,000 hour LED lighting system at 1500 lumens per metre in cabinet top and to each shelf
- Base ticket strip: 25mm

Operational Excellence

- Constructed from mild steel powdercoated satin black with fully double-glazed, toughened safety glass for maximum energy efficiency, climate control and durability
- A High capacity EC (electronically controlled) energy saving and low noise fans
- Electronic controller ensures the cabinet is operating as efficiently as possible
- Cabinet features an 'air curtain' to retain cold air within cabinet
- Configured with a pre-filter with regular cleaning by operations staff the life of the cabinet can be extended
- Auto Condensate Removal (ACR)
- Fitted with protective black buffer rail at base front and sides
- Fitted with unidirectional rollers and adjustable stabilisers



Showing: Visair Upright refrigerated 700mm freestanding open front with three shelves and base

OPTIONS & ACCESSORIES

Contact a FPG Sales Representative for our full range, including:

- Two full-width shelf option
- Shelf: Colour and woodprint options available
- Shelf ticket strip: 30mm
- Custom colour
- Branded decals
- Lockable castors
- Gravity feed system
- Night curtain
- Custom joinery solution





















UPRIGHT 700 OPEN FRONT

REFRIGERATED: R290

REFRIGERATION DATA

MODEL	CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	REFRIGERATION	REFRIGERANT	A LIMIT	CONDENSATE REMOVAL
IN-VA07-BXXX	+2°C - +4°C	Climate Class 3 - 25°C / 60% RH	Integral	R290	N/A	ACR

ELECTRICAL DATA

MODEL	VOLTAGE PHASE	SE CURRENT	E24H	kWh per hour	IP	MAINS		LED LIGHTING					
MODEL	VOLIAGE	FIIASE	CORREIVI	(kWh)	(kWh)	(average)	(average)	age) RATING	CONNECTION	CONNECTION PLUG1	HOURS	LUMENS	COLOUR
IN-VA07-BXXX	220-240 V	Single	6.2 A	15.83	0.65	IP 22	3 metre, 3 core cable	10 amp, 3 pin plug	50,000	1500 per metre	Natural		

¹Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-VA07-BXXX	0.86 m ²	3 Shelves + Base	Open front	N/A	Stainless 304 and mild steel

DIMENSIONS

1431 O/A APPLIANCE

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-VA07-BXXX	1431 x 706 x 816	- kg

Crated weights and dimensions vary. Please contact us for information on your shipment.

Installation note: Designed to be installed as a stand alone unit.

UNOBSTRUCTED AIRFLOW MUST BE MAINTAINED TO ENSURE UNIT PERFORMANCE AND TO MAINTAIN WARRANTY. ALLOW NO LESS THAN 200mm CLEARANCE ABOVE CABINET FOR AIRFLOW.




PLAN VIEW

706 O/A APPLIANCE

615 SHELF WIDTH

154

493




FRONT ELEVATION SECTION VIEW

REAR TOP VENTILATION



PLAN VIEW - AIRFLOW





More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at sales@fpgworld.com or visit www.fpgworld.com for full contact details for your region.



82

CABLE EXIT REAR, **CABLE LENGTH 3m**

33

