FPG

FPGWORLD.COM

visair

UPRIGHT 1800
OPEN FRONT - TALL HEIGHT
HEATED WITH 3 SHELVES

RANGE	VISAIR UPRIGHT
TEMPERATURE	HEATED
MODEL	IN-VH18-A004
FRONT	OPEN FRONT
INSTALLATION	FREESTANDING/ROLLERS
HEIGHT	1900mm
WIDTH	1865mm
DEPTH	736mm

TEMPERATURE RANGE	+65˚C – +85˚C
RECOMMENDED CORE PRODUCT TEMPERATURE	+65˚C – +80˚C
ENVIRONMENTAL TEST CONDITIONS	22˚C / 65% RH

FEATURES

- **High energy efficiency: 4.52 kWh per hour (average)**
- **Cabinet operating temperature range +65˚C - +85˚C**
  Recommended core product temperature +65˚C - +80˚C
- Robust open front display, powdercoated satin black for a sleek finish

Open Front Heated Display

- Display area starts at 734 mm (height) for easier access to hot product
- Four full-width display levels: three fixed **IWave** quartz infrared shelves and heated base
- Each **IWave** shelf is brushed stainless steel and is fitted with ticket strip to front: 30mm (height), with caution decal applied. Each shelf is supplied with 2x 855mm width removable aluminium drip trays
- Pluggable 25,000 hour LED lighting system at 2758 lumens per metre in cabinet top and to each shelf
- Base ticket strips: 30mm (height) with caution decal applied

Operational Excellence

- FPG **IWave** heating technology uses low-wattage quartz infrared elements complemented with a heating coil in the base for even temperature distribution and extended shelf life
- Fitted with an electronic controller for energy efficiency
- Safer for consumers - display surfaces are maintained < +65˚C and the internal air temperature is lower than in many fan-assisted cabinets
- No noise pollution – this cabinet runs silently
- Constructed from stainless and mild steel with fully double-glazed, toughened safety glass for maximum energy efficiency, climate control and durability
- Fitted with protective black buffer rail, stainless steel toe kick and rubber floor skirt at base front and sides
- Fitted with unidirectional rollers and adjustable stabilisers

Indicates sustainability benefits

IWave

Showing : Visair Upright heated 1800mm freestanding open front tall height cabinet with three **IWave** shelves and base

OPTIONS & ACCESSORIES

Contact a **FPG Sales Representative** for our full range, including:

- Drip trays: Colour and woodprint options available
- Custom colour
- Branded decals
- Lockable castors
- Custom joinery solution

ASNZ Standards FOOD Standards CE IEC

Please contact FPG to discuss your requirements for meeting country-specific standards.

FPG
FPGWORLD.COM

visair

UPRIGHT 1800
OPEN FRONT - TALL HEIGHT
HEATED WITH 3 SHELVES

HEATED DATA

MODEL	TEMPERATURE RANGE	RECOMMENDED CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	IWAVE HEATING
IN-VH18-A004	+65˚C - +85˚C	+65˚C - +80˚C	22˚C / 65% RH	Low-wattage infrared quartz elements

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT[1]	E24H[2] (kWh)	kWh per hour average	kWh per hour per m²	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG	HOURS	LUMENS	COLOUR
IN-VH18-A004	220-240 V	Single	26.3	108.39	4.52	1.55	Fixed wiring[3]	N/A	25,000	2758 per metre	Natural

[1]Current is the maximum potential current draw at 240v with +5% element tolerance.
[2]Nominal power consumption per 24h. i.e: 230V at 0% energy tolerance.
[3]Please see manual for more information.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	SHELF DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION	IP RATING
IN-VH18-A004	2.91 m²	3 Shelves + Base	Open front	N/A	Stainless 304 and mild steel	IP 22

DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-VH18-A004	1900 x 1865 x 736	320 kg

Crated weights and dimensions vary. Please contact us for information on your shipment.



PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

For information on technical data and installation guidelines please contact support@fpgworld.com

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at **sales@fpgworld.com** or visit **www.fpgworld.com** for full contact details for your region.

Worldwide contact details:

 © 2025 Future Products Group Limited