FPG
FPGWORLD.COM

# ENCORE

## SERIES 8 SQUARE
## IN-COUNTER 1500
## CONTROLLED AMBIENT: R290 **VSD**

| | | |
|---|---|---|
| **RANGE** | ENCORE SERIES 8 | |
| **TEMPERATURE** | CONTROLLED AMBIENT | |
| **MODEL** | IN-EC15-CA-08-B104 | IN-EC15-CA-08-B105 |
| **FRONT** | SQUARE/<br>TILT FRONT | SQUARE/<br>SLIDING DOORS |
| **INSTALLATION** | IN-COUNTER | |
| **REFRIGERATION** | INTEGRAL, R290 | |
| **TECHNOLOGY** | VARIABLE SPEED DRIVE (VSD) | |
| **HEIGHT** | 1260mm | |
| **WIDTH** | 1500mm | |
| **DEPTH** | 662mm | |

| | |
|---|---|
| **CORE PRODUCT TEMPERATURE** | +16˚C – +18˚C |
| **ENVIRONMENTAL TEST CONDITIONS** | CLIMATE CLASS 3<br>25˚C / 60% RH |

## FEATURES

- **Maximum energy efficiency: 0.21 kWh per hour (average)**
- **Maintains an average of +16˚C - +18˚C core product temperature at Climate Class 3: 25˚C/60%RH**
- Smart display with double-glazed glass finished with a black trim

### Tilt Front or Sliding Doors Controlled Ambient Display

- Three tiltable, height-adjustable stainless steel shelves and base are full cabinet width to support maximum display capacity
- 50,000 hour LED lighting system at 1500 lumens per metre in cabinet top and to each shelf
- Unique front ticket strip holders 30mm on shelves and base, and to the rear of shelves

### Operational Excellence

- Sliding doors (staff side) and tilt front or sliding doors options (customer side)
- High internal humidity maintains and extends shelf life
- Constructed from stainless and mild steel with fully double-glazed, low-E coated, toughened safety glass for maximum energy efficiency, climate control and durability
- Variable speed drive inverter compressor and electronic controller ensure the cabinet is operating as efficiently as possible
- Configured with a pre-filter - with weekly cleaning by operations staff the life of the cabinet can be extended
- Auto condensate removal
- FPG Freeflow air ventilation at rear eliminates the need for front ventilation panels
- Designed to be installed into joinery

Showing : Encore Series 8 controlled ambient 1500mm square in-counter tilt front with integral refrigeration

## OPTIONS & ACCESSORIES

Contact a **FPG Sales Representative** for our full range, including:

- Shelf trays: glass or mild steel. Powdercoat colour and woodprint options available for steel.
- Branded decals
- Shelf ticket strips: powdercoat colour
- Forward-facing controls
- Sides: mirror effect
- Rear Sling Doors that slide and swing
- Pull-out shelves
- Custom joinery solution

Indicates sustainability benefits

ASNZ Standards | FOOD Standards | CE | IEC | MEPS

Please contact FPG to discuss your requirements for meeting country-specific standards.

FPG
FPGWORLD.COM

# ENCORE

## SERIES 8 SQUARE
## IN-COUNTER 1500
## CONTROLLED AMBIENT: R290 **VSD**

### REFRIGERATION DATA

| MODEL | CORE PRODUCT TEMPERATURE | ENVIRONMENTAL TEST CONDITIONS | REFRIGERATION | REFRIGERANT | A LIMIT | CONDENSATE REMOVAL |
|---|---|---|---|---|---|---|
| IN-EC15-CA-08-B1xx | +16˚C – +18˚C | Climate Class 3 - 25˚C / 60% RH | Integral - VSD | R290 | N/A | Automatic |

### ELECTRICAL DATA

| MODEL | VOLTAGE | PHASE | CURRENT | E24H (kWh) | kWh per hour (average) | IP RATING | MAINS | | LED LIGHTING | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | CONNECTION | CONNECTION PLUG[1] | HOURS | LUMENS | COLOUR |
| IN-EC15-CA-08-B1xx | 220-240 V | Single | 2.6 A | 5.08 | 0.21 | IP 21 | 3 metre, 3 core cable | 10 amp, 3 pin plug | 50,000 | 1500 per metre | Natural |

[1]Please advise country to change plug specification.

### CAPACITY, ACCESS & CONSTRUCTION

| MODEL | SHELF DISPLAY AREA | LEVELS | ACCESS FRONT | ACCESS REAR | CHASSIS CONSTRUCTION |
|---|---|---|---|---|---|
| IN-EC15-CA-08-B104 | 2.16 m² | 3 Shelves + Base | Tilt front | Sliding doors | Stainless 304 and mild steel |
| IN-EC15-CA-08-B105 | | | Sliding doors | | |

### DIMENSIONS

| MODEL | H x W x D mm (Uncrated) | MASS (Uncrated) |
|---|---|---|
| IN-EC15-CA-08-B104 | 1260 x 1500 x 662 | 211 kg |
| IN-EC15-CA-08-B105 | | 210 kg |

Crated weights and dimensions vary. Please contact us for information on your shipment.

**Installation note:**

Model cutout dimensions: IN-EC15-CA-08-B104 & B105 models require 1476 x 650mm benchtop cutout (see product manual for installation guide). Please request a thermal film when installing a controlled ambient cabinet next to an adjacent refrigerated cabinet. **UNOBSTRUCTED AIRFLOW MUST BE MAINTAINED TO ENSURE UNIT PERFORMANCE AND MAINTAIN WARRANTY.**




PLAN VIEW




PLAN VIEW
FREEFLOW AIR TECHNOLOGY




FRONT ELEVATION




SECTION VIEW




REAR ELEVATION

**For information on technical data and installation guidelines please contact support@fpgworld.com**

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at **sales@fpgworld.com** or visit **www.fpgworld.com** for full contact details for your region.

Worldwide contact details:

 © 2026 Future Products Group Limited