FPG
FPGWORLD.COM

ENCORE

SERIES 8 SQUARE
IN-COUNTER 1500
HEATED

RANGE	ENCORE SERIES 8	
TEMPERATURE	HEATED	
MODEL	IN-EC15-H-08-A005	IN-EC15-H-08-A006
FRONT	SQUARE/ TILT FRONT	SQUARE/ SLIDING DOORS
INSTALLATION	IN-COUNTER	
HEIGHT	951mm	
WIDTH	1500mm	
DEPTH	662mm	

TEMPERATURE RANGE	+55˚C – +80˚C
RECOMMENDED CORE PRODUCT TEMPERATURE	+65˚C – +80˚C
ENVIRONMENTAL TEST CONDITIONS	22˚C / 65% RH

FEATURES

- **High energy efficiency: 0.70 kWh per hour (average)**
- **Cabinet operating temperature range +55˚C – +80˚C Recommended core product temperature +65˚C – +80˚C**
- Smart display with double-glazed glass finished with a black trim

Tilt Front or Sliding Doors Heated Display

- Four tiltable, height-adjustable stainless steel wire rack shelves are full cabinet width to support maximum display capacity
- 25,000 hour LED lighting system at 2758 lumens per metre in cabinet top and to each shelf
- Unique shelf mounted front ticket strip 30mm together with rear ticket holder

Operational Excellence

- Sliding doors (staff side) and tilt front or sliding doors options (customer side)
- Constructed from stainless and mild steel with fully double-glazed, low-E coated, toughened safety glass for maximum energy efficiency, climate control and durability
- Low wattage density element provides even temperature distribution
- Designed to be installed into joinery

Showing : Encore Series 8 heated 1500mm square in-counter tilt front

OPTIONS & ACCESSORIES

Contact a **FPG Sales Representative** for our full range, including:

- Shelf trays: Toughened safety glass or mild steel. Colour and woodprint options available for steel.
- Stainless steel product trays
- Stainless steel pie chutes
- Branded decals
- Shelf ticket strips: powdercoat colour
- Forward-facing controls
- Sides: mirror effect
- Rear Sling Doors that slide and swing
- Custom joinery solution

Indicates sustainability benefits

ASNZ Standards FOOD Standards CE IEC

Please contact FPG to discuss your requirements for meeting country-specific standards.

FPG

FPGWORLD.COM

ENCORE

SERIES 8 SQUARE
IN-COUNTER 1500
HEATED

HEATED DATA

MODEL	TEMPERATURE RANGE	RECOMMENDED CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	HEATING
IN-EC15-H-08-Axxx	+55˚C – +80˚C	+65˚C – +80˚C	22˚C / 65% RH	Low-wattage density element

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24H (kWh)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG[1]	HOURS	LUMENS	COLOUR
IN-EC15-H-08-Axxx	220-240 V	Single	12.9 A	16.88	0.70	IP 21	3 metre, 3 core cable	15 amp, 3 pin plug	25,000	2758 per metre	Natural

[1]Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	SHELF DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-EC15-H-08-A005	2.19 m²	4 Shelves	Tilt front	Sliding doors	Stainless 304 and mild steel
IN-EC15-H-08-A006			Sliding doors		

DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-EC15-H-08-A005	951 x 1500 x 662	172 kg
IN-EC15-H-08-A006		172 kg

Crated weights and dimensions vary. Please contact us for information on your shipment.

Installation note:

Model cutout dimensions: IN-EC15-H-08-A005 & A006 models require 1478 x 650mm benchtop cutout (see product manual for installation guide).



PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

For information on technical data and installation guidelines please contact support@fpgworld.com

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at **sales@fpgworld.com** or visit **www.fpgworld.com** for full contact details for your region.

Worldwide contact details:

 © 2026 Future Products Group Limited