FPG
FPGWORLD.COM

IMPULSE PLUS

13H 06W
FRONT SWING DOORS/2 SHELVES
REFRIGERATED: R290 **VSD**

RANGE	IMPULSE SERIES
TEMPERATURE	REFRIGERATED
MODEL	IN-VI06-R-13-06-B2xx
FRONT	SWING DOORS
INSTALLATION	FREESTANDING/ROLLERS
REFRIGERATION	INTEGRAL, R290
TECHNOLOGY	VARIABLE SPEED DRIVE (VSD)
HEIGHT	1350mm
WIDTH	600mm
DEPTH	600mm

CORE PRODUCT TEMPERATURE	+1˚C – +3˚C
ENVIRONMENTAL TEST CONDITIONS	CLIMATE CLASS 3 25˚C / 60% RH
CABINET CLASSIFICATION	3M0

ENERGY EFFICIENCY

NZ & AU Star Rating

10 ENERGY RATING

FEATURES

- **Maximum energy efficiency: 0.09 kWh per hour (average)**
- **Maintains an average of +1˚C – +3˚C core product temperature at Climate Class 3: 25˚C/60% RH**
- Compact display with swing doors (customer side), powdercoated satin black for a sleek finish

Swing Doors Refrigerated Display

- Three display levels: two height adjustable shelves and base are powdercoated black and full cabinet width to support maximum display capacity
- Pluggable 50,000 hour LED lighting system at 800 lumens per metre in cabinet top, each shelf and to base
- Shelf and base ticket strips: 30mm

Operational Excellence

- Constructed from stainless steel and powdercoated mild steel with fully double-glazed, low-E coated, toughened safety glass for maximum energy efficiency, climate control and durability
- Fitted with high capacity EC (electronically controlled) energy saving and low noise fans
- Variable speed drive inverter compressor and electronic controller ensure the cabinet is operating as efficiently as possible
- Configured with a pre-filter - with weekly cleaning by operations staff the life of the cabinet can be extended
- Auto Condensate Removal (ACR)
- Fitted with unidirectional rollers

Showing : Impulse Plus 13H 06W refrigerated freestanding with front swing doors and two shelves and base

OPTIONS & ACCESSORIES

Contact a **FPG Sales Representative** for our full range, including:

- Add/remove shelves
- Shelf: Colour and woodprint options available
- Custom colour
- Branded decals
- Lockable castors

Indicates sustainability benefits

ASNZ Standards FOOD Standards CE IEC MEPS

Please contact FPG to discuss your requirements for meeting country-specific standards.

FPG
FPGWORLD.COM

IMPULSE PLUS

13H 06W
FRONT SWING DOORS/2 SHELVES
REFRIGERATED: R290 **VSD**

REFRIGERATION DATA

MODEL	CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	REFRIGERATION	REFRIGERANT	A LIMIT	CONDENSATE REMOVAL
IN-VI06-R-13-06-B2xx	+1°C – +3°C	Climate Class 3 - 25°C / 60% RH	Integral - VSD	R290	N/A	ACR

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24H (kWh)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG[1]	HOURS	LUMENS	COLOUR
IN-VI06-R-13-06-B2xx	220-240 V	Single	1.2 A	2.27	0.09	IP 21	3 metre 3 core cable	10 amp 3 pin plug	50,000	800 per metre	Natural

[1]Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	SHELF DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-VI06-R-13-06-B2xx	0.58 m^2	2 Shelves + Base	Swing doors	N/A	Mild steel and double-glazed safety glass

DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-VI06-R-13-06-B2xx	1350 x 600 x 600	119 kg

Crated weights and dimensions vary. Please contact us for information on your shipment.

Installation note; Designed to be installed as a stand alone unit or in an island matrix. Please request a thermal film when installing a refrigerated cabinet next to an adjacent refrigerated cabinet. **UNOBSTRUCTED AIRFLOW MUST BE MAINTAINED TO ENSURE UNIT PERFORMANCE AND TO MAINTAIN WARRANTY. WHEN PLACED AGAINST A WALL OR IN AN ISLAND MATRIX AIRFLOW VENTING IS RE-DIRECTED TO TOP OF CABINET. ALLOW NO LESS THAN 200mm CLEARANCE ABOVE CABINET FOR AIRFLOW.**



PLAN VIEW



SECTION VIEW



PLAN VIEW - AIRFLOW



FRONT ELEVATION



REAR ELEVATION

For information on technical data and installation guidelines please contact support@fpgworld.com

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at **sales@fpgworld.com** or visit **www.fpgworld.com** for full contact details for your region.

Worldwide contact details:

 © 2026 Future Products Group Limited